

DON'T TIE DOWN ... TIE UP



We want to thank you for your purchase of the **Cranky Horse Swivel!** We are striving very hard as a company, to help horse owners learn about our awesome product! We appreciate any and all referrals that you can give! If you have any questions, concerns, or comments, please contact us at crankyhorseranch@gmail.com

INSTALLATION INSTRUCTIONS

1. The **Cranky Horse Swivel** is designed to fit any round or square wooden post that is 5 1/2" in diameter or bigger. The installation on a metal post will require welding.
2. We recommend using a 12' post for the **Cranky Horse Swivel** to work properly for the average size horse.
3. When you are ready to set your post, make sure that you have 4' of the post in the ground, and 8' exposed above the ground.
4. If you are unable to dig your hole for your post exactly 4', dig as deep as you can and install your post. Then measure from the ground up 8' and cut off your post so you can get the required result.
5. When you dig your hole, make it wide enough at the bottom to allow plenty of concrete to be able to form around it.
6. Your swivel comes with a protective band around the swivel's base. This is put in place to prevent damage to the swivel while being installed. Please remove after installation.
7. Place your swivel on top of the post and attach the swivel using the provided patented custom lag bolts. Or you can concrete your post, and then install your swivel. (Your preference)

8. When installing the lag bolts, make sure they are positioned as far away from the swivel housing as possible to insure proper movement of swivel. Make sure after you have installed the lag bolts, that the bolt heads are flush with the swivel's base.
9. When you install your post, make sure that you brace and level it before you add the concrete. We recommend letting the concrete cure 24-48 hours before use.
10. Be sure that you purchase the appropriate chain and quick link for your swivel. For the chain, we recommend 1/4" thick minimum by 61" length for the average size horse, and 5/16" quick link.
11. To attach the chain, put the quick link onto the chain and attach it onto the shackle. Now attach the shackle to the swivel arm, making sure that the plastic bushings are placed on the inside of the shackle and next to the swivel arm. This provides protection to keep the chain from colliding with the inside of the shackle. Tighten the shackle bolt and quick links with a wrench after you have finished to prevent loosening and for safety.
12. The **Cranky Horse Swivel** is designed to be used only with a chain. It will **NOT** function properly with any type of rope!
13. Due to assembly or handling during shipping, the swivel arm may not fit into the appropriate slot on the swivel's base. Some adjustment may be required.

The **Cranky Horse Swivel** is guaranteed to be free of any defects and fully functional upon your purchase. If you are dissatisfied in any way, please contact us so that the necessary arrangements can be made to insure your full satisfaction!

If items are being returned due to the buyer's remorse, the shipping cost must be covered by the buyer. The original shipping cost, and a 15% restocking fee, will be deducted from the refund. All returns must be made within (14) days of the delivery date. If any returns that are the result of the seller's error, the buyer will receive a full refund of the item, plus shipping cost.



www.crankyhorse.com

crankyhorseranch@gmail.com

CRANKY HORSE IS A REGISTERED TRADEMARK * ALL PATENTS PENDING**